



Policy

Saskatoon & Area - Occupational Health & Safety

Number: 53-014

Title: Physical Hazard: Fall Protection

Saskatchewan Employment Act:

OHS Regulation: 101-107, 116

Date: January 1, 2017

Date Revised/Reaffirmed: June 5, 2018

Any PRINTED version of this document is only accurate up to the date of printing. Saskatoon Health Authority (SHA), Occupational Health & Safety Services (OHS) cannot guarantee the currency or accuracy of any printed policy. Always refer to the Occupational Health & Safety internal website for the most current versions of documents in effect. This policy complies with legislation (minimum standards) at the time of this writing and/or revision. SHA OHS accepts no responsibility for use of this material by any person or organization not associated with SHA. No part of this document may be reproduced in any form for publication without permission of SHA OHS Services.

Purpose

To ensure that all contractors and workers are protected from falling and will be safe in the event of an accidental fall

Roles and Responsibilities

Employer must ensure:

- That if a lifeline is used all conditions in 101(1)(2)(3)(4) of the OHS regulations are followed
- That all components of the fall arrest system are approved and maintained
- That the fall arrest system prevents:
 - A worker from falling more than 1.2m without a shock absorber
 - A fall no more 2 meters when a shock absorber is used or the limit specified in the manufacturers specifications, whichever is less
 - Applies a peak fall arrest force of no more than 8 kilonewtons to the worker
 - Is fastened to a lifeline or secure anchor point that has a breaking strength of 22.2 kilonewtons

Manager/Supervisor must ensure:

- That roles and responsibilities of all workers are being met, as well as applicable legislation and/or standards
- Safe work procedures are written and followed
- The full body harness and linkage are approved and maintained
- That the full body harness is a proper fit to the worker
- Worker has been trained in the use of all components of the fall arrest system
- That a protective thimble is used to protect ropes and straps from chafing when a rope or strap is used
- That any snap hooks that are a part of the fall arrest system are self locking
- That a lanyard is as short as conditions permit
- The lanyard is constructed of the proper materials and has the suitable snap hooks
- The lanyard is approved and maintained

Worker must ensure:

- They are trained in and follow the safe work procedures
- They are trained in and use any PPE required (selection, use, care and handling)

- They inspect a lanyard or lifeline and the components of the fall arrest system and harness and ensure that it is free from all obstructions in Regulation 106(1-4), 107(2) of the OHS Regulations prior to use
- They report to their supervisor and the Safety Alert System/Incident Report Line any incidents or near misses involving fall protection

Orientation & Training

- Fall Protection training course
- Training in the inspection care and use of all parts of the personal fall arrest system

Materials

- Appropriate fall arrest system

Non-Compliance/Breach:

Non-compliance with this policy will result in a review of the incident. A review for non-compliance may result in disciplinary action, up to and including termination of employment or privileges; fines and /or prosecution of individuals under the Saskatchewan Employment Act and OHS Regulations.

References

- This policy is used in conjunction with Policy 53-028 Working at Heights

Review Dates:

January 1, 2017

June 5, 2018